FS-135

Detailed Specifications

Type	Single Staple Finisher					
Installation	Freestanding					
Alignment	Center					
Output Tray	1st, Elevator Tray					
Setting Mode	Non-Sort, Sort, Sort Staple					
Performance	Non-Sort	Output Tray	Elevator Tray			
		Paper Type	Plain Paper: 64 to 90 g/m^2 (17 to 24 lbs.)	Thick Paper 1: 91 to 150 g/m^2 (24-1/4 to 40 lbs.)	Special Paper: Envelopes, Transparencies, Labels	
				Thick Paper 2: 151 to 209 g/m^2 (40-1/4 to 55 1/2 lbs.)		
				Thick Paper 3: 210 to 256 g/m^2 (55-3/4 to 68 lbs.)		
		Paper Size	Inch area	5-1/2×8-1/2L/C, 7-1/4×10-1/2L/C, 8.5×11L/C, 8.5×14L, 11×17L, 12-/1/4×18L		
			Metric area	A4L/C, A3L, A3WideL		
			CD	Min.: 90 mm, Max.: 330.2 mm		
			FD	Min.: 139.7 mm, Max.: 482.6 mm		
		Capacity	Plain Paper: 250 sheets (A4L or 8.5×11L), 150 sheets (More than B4L or 8.5×14L) Thick paper, Special paper: 20 sheets			
		Empty Detection	No			
		Full Detection	Yes			
	Sort	Output Tray	Elevator Tray			
		Shift	Amount of shift: 30 mm			
		Paper Type	Plain Paper: 64 to 90 g/m^2 (17 to 24 lbs.)	Thick Paper 1: 91 to 150 g/m^2 (17-1/4 to lbs.)		
				Thick Paper 2: 151 to 209 g/m^2 (40-1/4 to 55 1/2 lbs.)		
		Paper Size	Inchi area	7-1/4×10-1/2L/C, 8.5×11L/C, 8.5×14L, 11×17L, 12-/1/4×18L		
			Metric area	A4L/C、B4L、A3L、A3WideL		
			CD	Min.: 182 mm, Max.: 330.2 mm		
			FD	Min.: 182 mm, Max.: 482.6 mm		
		Capacity	1000 sheets (Less than A4L or 8.5×11L), 500 sheets (More than B4L or 8.5×14L)			
		Empty Detection	No			
		Full Detection	Yes			
	Sort Staple	Output Tray	Elevator Tray			
		Paper Type	Plain Paper: 64 to 90 g/m^2 (17 to 24 lbs.)	*Thick Paper 1: 91 to 150 g/m^2 (17-1/4 to lbs.)		
				*Thick Paper 2: 150 to 209 g/m^2 (40-1/4 to 55 1/2 lbs.)		
		Paper Size	Inch area	8.5×11L/C, 8.5×14L, 11×17L		
			Metric area	A4T/Y、A3T		
			CD	Min.: 182 mm, Max.: 297 mm		
			FD	Min.: 182 mm, Max.: 431.8 mm		
		Capacity	1000 sheets (Less than A4L or 8.5×11L), 500 sheets (More than B4L or 8.5×14L			
		Staple Position	Inch area	Rear corner (Diagonal)	8.5×11C, 11×17L	
				Rear corner (Parallel)	8.5×11L, 8.5×14L	
			Metric area	Rear corner (Diagonal)	A4Y、A3T	
				Rear corner (Parallel)	A4T	
		Number of Sheets Bound	Standard mode	2 to 30 sheets		
			Cover mode	1. 209 g/m^2 (NS1000C): 2 sheets + 90 g/m^2 (Original 90): 13 sheets 2. 209 g/m^2 (NS1000C): 2 sheets + 90 g/m^2 (New Radiate White): 18 sheets 3. 209 g/m^2 (NS1000C): 2 sheets + 80 g/m^2 (CF80): 22 sheets 4. 209 g/m^2 (NS1000C): 2 sheets + 80 g/m^2 (Copy Paper 80): 28 sheets		
			Color Wise: 20 sheets×20 copies			
		Empty Detection	No			
		Full Detection	Yes			
Power Source	DC24V±5% (supplied by copier)					
Power Consumption	Less than 63 W					
Dimension	Width: 538 mm (21 in.) Depth: 637mm (24-3/4in.) Height: 978 mm (38-1/2 in.)					
Weight	Finisher: 32.9 kg (72-1/2 lbs.) Horizontal Transport Unit: 2.6 Kg (5-3/4 lbs.) Total: 35.5 kg (78-1/4 lbs.)					
Supplies	1 Stapling cartridge (3000 staples for 30 sheets)					
Environmental Requirements	Same as copier					

*: Cover Mode only