
3-2. ADJUSTMENT REQUIREMENTS LIST

Adjustment Item	Requirements	Adjusting Point	Ref. Page.
Shading Position		Control Panel	D-43
Print / Regist (FD)	3.5 ± 0.2mm	Control Panel	D-36
IR / Regist (CD)	—	Control Panel	D-39
IR / Regist (FD)	—	Control Panel	D-40
IR / Zoom (CD)	× 2.00 : 200 ± 2mm × 1.00 : 200 ± 2mm × 0.50 : 100 ± 1mm	Control Panel	D-41
IR / Zoom (FD)	× 2.00 : 200 ± 2mm × 1.00 : 300 ± 3mm × 0.50 : 150 ± 1.5mm	Control Panel	D-42
Manual Bypass Table Reference Position	10.8 ± 0.5mm	Manual Bypass Table	D-37
1st and 2nd Drawer Reference Position	10.8 ± 0.5mm	Drawer Cover	D-38
Adjustment of the Paper Lifting Plate Position	—	Spring Position	D-45
Adjustment of the Scanner/Mirrors Carriage Position	—	Scanner/Mirrors Carriage Position	D-46
Adjustment of the Doctor Blade	0.35 $^{+0.07}_{-0}$ mm	Doctor Blade	D-47
Adjustment of the Original Size Detecting Board	—	Control Panel	D-48

3-3. ADJUSTMENT OF SWITCHES

(1) Adjustment of Front Door Interlock Switch S2



1. Loosen screws that secure the Front Door Interlock Switch Actuating Plate to the Front Door.