<table>
<tr><th>Choice No.</th><th>Setting (The default is Highlighted).</th></tr>
<tr><td>20</td><td>
<LEADING EDGE ERASE>
Adjust to vary the width of erase on the leading edge.
<table>
<tr><th>Data</th><th>Description</th><th>Data</th><th>Description</th></tr>
<tr><td>2</td><td>Erase width approx. 2 mm</td><td>4</td><td>Erase width approx. 4 mm</td></tr>
<tr><td>3</td><td>Erase width approx. 3 mm</td><td>5</td><td>Erase width approx. 5 mm</td></tr>
</table>
</td></tr>
<tr><td>21</td><td>
<TRAILING EDGE ERASE>
Adjust to vary the width of erase on the trailing edge.
<table>
<tr><th>Data</th><th>Description</th><th>Data</th><th>Description</th></tr>
<tr><td>2</td><td>Erase width approx. 2 mm</td><td>4</td><td>Erase width approx. 4 mm</td></tr>
<tr><td>3</td><td>Erase width approx. 3 mm</td><td>5</td><td>Erase width approx. 5 mm</td></tr>
</table>
</td></tr>
<tr><td>23</td><td>
<LOOP ADJUST>
Adjust to vary the length of the loop to be formed in paper before the Synchronizing Rollers.
<table>
<tr><td>Data</td><td>97</td><td>98.....</td><td>100</td><td>.....103</td><td>104</td></tr>
<tr><td>Description</td><td>4.9</td><td>5.5.....</td><td>7.0</td><td>.....9.1</td><td>9.8</td></tr>
</table>
The length is variable in 0.1-mm increments.
</td></tr>
<tr><td>31/37/38</td><td>
<ORIGINAL STOP POSITION ADJUSTMENT>
Adjust the position at which to stop the original in each of the following ADF modes.
31: ORIG. STOP POSITION 1 (1-sided originals)
37: ORIG. STOP POSITION 2 (S-ADF mode)
38: REGIST LOOP (ADF)
<table>
<tr><td>Data</td><td>93</td><td>92.....</td><td>100</td><td>.....107</td><td>108</td></tr>
<tr><td>Description</td><td>-7</td><td>-6.....</td><td>0</td><td>.....+7</td><td>+8</td></tr>
</table>
The position is variable in 1-mm increments.
NOTE
The stop position is farther away from the Original Width Scale and the loop length of Regist. Loop (ADF) is greater in the + direction.
</td></tr>
</table>