

(11) Adjustment of Single-Sided Book second page Leading Edge Registration


◆Requirement




- A copy of reference dimension A (width 20 mm), shown in the left figure, of an A3 test chart, should have a width of 20 ±3.0 mm on the second page. Note that B = C.
- Setting range: 45-55
- Unit of image leading edge movement (on the second page): 0.4 mm




1. Place the test chart face down on the Original Glass and align its rear left corner with the reference position marker on the Original Width Scale on the left side of the platen. Close the Original Cover.



2. Open the System Panel.
3. Press the Book Mode key once to select Book 1 (single-sided) mode.
4. In the full size mode (x1.000), make two single copies on A4 crosswise or 11" x 8-1/2" paper.
   Check the second page of the second copy for leading edge registration. If the registration error is outside the tolerance of 20 ±3.0 mm, go to step 5.



5. On the Control Panel, press the Stop Key, Multi-Copy Key 0, Stop Key and Multi-Copy Key 1, in that order. The copier enters the Tech. Rep. Program mode.
6. Press Multi-Copy key 1, Stop key and then Start key to enter the adjustment mode.



7. Press the OK key repeatedly until the Display Panel shows the message "Book B-Scan Regist. : (A 6)".
8. Note the value shown below the message and then press the Clear key to clear the current setting.
9. Using the Multi-Copy keys, increase or decrease the setting with respect to the noted value, for the correct dimension A on the copy: