POWER/CURRENT CONSUMPTION (Copier Only):

Voltage	Exposure Lamp (Rating)	Fusing Heater Lamp (Rating)	Max. Power Consum-ption	In Standby	Max. Current Consum-ption
115, 127 V	80 V 230 W	115, 127 V 850 W	1240 W	900 W	11.2 A (115 V) 10.1 A (127 V)
120 V	80 V 230 W	120 V 850 W	1290 W	960 W	11.2 A
200 ~ 220 V	160 V 250 W	200 V 850 W	1260 ~ 1400 W	940 ~ 1070 W	6.7 A
220 ~ 240 V	160 V 250 W	200 V 850 W	1260 ~ 1390 W	940 ~ 1070 W	6.1 A

POWER REQUIREMENT : 115 V, 120 V, 127 V, 200 V, 220 V, 230 V, 240 V; 50/60 Hz

ENVIRONMENTAL CONDITIONS:

Temperature	10 to 35°C with a fluctuation of 10°C or less per hour
Humidity	15 to 85% RH with a fluctuation of 20% RH or less per hour
Ambient Illumination	3,000 lux or less
Levelness	1° (1.75 mm/100 mm)

DIMENSIONS : Width .... 620 mm
Depth .... 685 mm
Height ... 602 mm (including Original Glass)

WEIGHT : 75 kg
(excluding the Exit Tray, starter, toner, and copy paper)

STANDARD ACCESSORIES : Operator's Manual, Setting-up Instructions, Starter, Exit Tray, User's Choice Card*1.
"*1. Except Europe"