### 11-2-6. 2-in-1 Erase

When only a single original is placed on the Original Glass in the 2-in-1 mode (using Duplexing/Automatic Document Feeder), the copier erases the area where no originals are present.

Different controls are provided depending on whether "Odd" is specified on the control panel for the number of originals to be used.

If "Odd" is specified, all LEDs are turned ON and kept ON for a given period of time after SCP Board PWB-J has generated an Image Leading Edge signal (BASE) to erase the first half page of the last original.

| Paper Size | A4C | A4L | A3L | A5C | B4L | B5L | B5C | 8.5" | 11" | 17" |
|---|---|---|---|---|---|---|---|---|---|---|
| Paper Length | 210 | 297 | 420 | 149 | 364 | 257 | 182 | 216 | 279 | 432 |
| Erase Time | 815 | 1105 | 1515 | 610 | 1330 | 970 | 720 | 835 | 1045 | 1555 |

Unit: Paper Length = mm, Timer = msec. L: Lengthwise; C: Crosswise

If "Odd" is not specified, all LEDs are turned ON after the lapse of a given period of time after PWB-J has generated a BASE signal to erase the last half page of the first original.

| Paper Size | A4C | A4L | A3L | A5C | B4L | B5L | B5C | 8.5" | 11" | 17" |
|---|---|---|---|---|---|---|---|---|---|---|
| Paper Length | 210 | 297 | 420 | 149 | 364 | 257 | 182 | 216 | 279 | 432 |
| Timer | 835 | 1125 | 1535 | 630 | 1350 | 990 | 740 | 855 | 1065 | 1575 |

Unit: Paper Length = mm, Timer = msec. L: Lengthwise; C: Crosswise