3-2. ADJUSTMENT REQUIREMENTS LIST

Adjustment Item	Requirements	Adjusting Point	Ref. Page
Optimum exposure in the Manual Exposure mode	Kodak Gray Scale: no image of the 1st step, faint image of the 2nd step	Control panel	D-73
Crosswise zoom ratio, full size	(×1.000) 200 ± 1.0 mm	Control panel	D-75
Feeding direction zoom ratio, full size	(×1.000) 300 ± 1.5 mm	Control panel	D-77
Multi Bypass Table reference Position	(×1.000) 20 ± 2.0 mm	Multi Bypass Table	D-79
1st Drawer reference Position	(×1.000) 20 ± 2.0 mm	Drawer Positioning Plate	D-80
2nd Drawer reference Position	(×1.000) 20 ± 2.0 mm	Drawer Positioning Plate	D-80
Leading edge registration, full size	(×1.000) 20 ± 1.5 mm	Control panel	D-81
Leading edge registration, enlargement	(×2.000) 40 ± 3.0 mm	Control panel	D-83
Leading edge registration, reduction	(×0.500) 10 ± 1.5 mm	Control panel	D-85
Leading edge registration, book second page	(×1.000) 20 ± 3.0 mm	Control panel	D-87
Image leading edge erase width	(×1.000) 1~6.5 mm	Control panel	D-89
Image trailing edge erase width	(×1.000) 0.5~5.5 mm	Control panel	D-91
Edge erase	(×1.000) 0.5~4.0 mm	Edge Erase Adjusting Screw	D-93