1 SPECIFICATIONS

TYPE : Console (with Stationary Platen)

PHOTOCONDUCTOR : Organic Photoconductor

COPYING SYSTEM : Electrostatic Dry Powdered Image Transfer to Plain Paper

PAPER FEEDING SYSTEM : 3-Way Feeding
- 1st Drawer: Fixed Paper Size Tray (500 sheets of paper, USA Area: 550 sheets of paper)
- 2nd Drawer: Universal Tray (500 sheets of paper, USA Area: 550 sheets of paper)
- Multi Bypass Table (50 sheets of paper)

EXPOSURE SYSTEM : Mirror Scanning, Slit Exposure

DEVELOPING SYSTEM : New Micro-Toning System

CHARGING SYSTEM : Comb Electrode DC Negative Corona with Scorotron System

IMAGE TRANSFER SYSTEM : Visible Image Transfer by means of a Single-Wire DC Negative Corona with Corotron System

PAPER SEPARATING SYSTEM : Single-Wire AC Corona with Corotron System, plus Paper Separator Finger

FUSING SYSTEM : Heat Roller

PAPER DISCHARGING SYSTEM : Charge Neutralizing Brush

MAXIMUM ORIGINAL SIZE : Metric-A3L; Inch-11" × 17"L (L: Lengthwise)

COPY MEDIUM

		1st Drawer (Automatic feeding)	2nd Drawer (Automatic feeding)	Multi Bypass Table
Medium	Plain paper (60 to 90 g/m^2)	○	○	○
	Translucent paper	–	–	○
	Transparencies	–	–	○
	Thick paper (91 to 157 g/m^2)	–	–	○
	Recycled paper	○	○	○
Dimensions	Maximum (Width × Length)	297 × 432 mm	297 × 432 mm	297 × 432 mm
	Minimum (Width × Length)	140 × 182 mm	140 × 182 mm	100 × 140 mm

○: Permissible –: Not permissible