RP Series Technical Bulletin

ISSUE NO.: RPT-007.doc

MODEL: RP3xxx Series DATE: 7 June, 2001

Data Category ☐Field Modification ☐Trouble Shooting ☒General Information ☐Safety Advice

Proceeding Grade	Parts Compatibility	Handling of Modified Parts
☐Action ASAP	☐Compatible	☐Free of Charge
☐Action as given	☐Conditionally Compatible	☐Conditionally Chargeable
☐Action if required	☐Not Compatible	☐Chargeable
☐Refer in need	☐Old Obsolete	

Our Ref.

SUBJECT: Program V1.32

BRIEF:

A new program, V1.32, has been been made.
This program is downloaded to our factory production machines starting from June 1, 2001.

Major Changes from V1.30

1. Added the following languages.
   Polish: #14 (can only be used for European or American models)
   Taiwanese: #4 (can only be used for Asian models)
   Indonesian: #7 (can only be used for Asian models)
2. Changed the default setting of the following test-modes.
   No. 481 (Paper-feed-clutch ON angle)
   The default setting has changed from “0” to “50”.
   Reason: We changed this setting for the new “W Scraper”, (refer technical bulletin RPT-006).
   No. 482 (Paper-feed-clutch OFF angle / Standard)
   The default setting has changed from “0” to “-50”.
   No. 484 (Paper-feed-clutch OFF angle / Light)
   The default setting has changed from “0” to “-70”.
   Reason: The paper-buckle between the first and second paper feed section was larger than the previous models. This was not good for some papers. Therefore, we have reduced the paper feed amount for *standard* and *light (thin)* paper.

IMPORTANT!!!

As the setting of test-mode does not return to the default setting unless you activate test-mode 82, the actual setting of test-mode 481, 482, and 484 will not change by just downloading this new program. You must activate test mode 82 to change the setting to the new default setting.

The application serial will be informed later.

Attached: